

# MANSION COMFORT

Herringbone

Mansion Comfort Natural Oak

2012980

75 x 15 cm  
7,5/0,55 mm

CE  
EN 14342-05

25 jaar  
Solidfloor™  
garantie



INTEGRATED  
SUBFLOOR  
INTEGRATED

## Packaging

Boards per pack:	12 boards
m <sup>2</sup> per pack:	1,35 m <sup>2</sup>
Weight per pack:	17 kg
Number of packs on a pallet:	36

## Dimensions

Length:	75 cm
Width:	15 cm
Thickness:	Total: 7,5 mm, including integrated sub floor Top layer: 0.55 mm

## Use

Usage class:	23 intensive domestic residential use 33 intensive commercial use
Floor heating (EN12524):	Yes, up to 27C°
Suitable for office chairs?:	Yes
Resistant to chemicals? (EN 423):	Yes, good
Acoustic reduction of impact sound:	Delat Lw: 15dB

## Specifications

Lightfastness (ISO 105-B02):	>6
Abrasion resistance (EN 660-2):	Group T
Heat transfer coefficient:	R=0,03m <sup>2</sup> k/w
Antistatic:	<2kV
Residual indentation (ISO 24343-1):	<0.05 mm
Dimensional stability:	<0.2%
Slip resistance (DIN 51130):	R9
Repetition factor:	6
Locking system:	5Gi
Bevel:	4-sided, micro bevel
Fire class:	Bfl-S1
VOC Emission:	A+

## Instructions and Maintenance

Maintain with Solidfloor™ Easy Protect & Solidfloor™ Easy Clean (visit [www.solidfloor.com](http://www.solidfloor.com) for more information).

All indicated values are guide values; production-dependent deviations cannot be avoided.